



EN AW-5754 [AlMg3]

d	l ⁺¹		Nr.		€/ 1.000
3,2	6,0	1,5 - 3,5	10730032060	500	59,52
	8,0	3,0 - 5,5	10730032080	500	64,92
	10,0	5,0 - 7,5	10730032100	500	74,05
	12,0	7,0 - 9,0	10730032120	500	79,68
	16,0	9,0 - 13,0	10730032160	500	88,12

d_k 9,5 ^{-0,3} **d_m 1,9** **k 1,2** ^{+0,5}  3,3 mm  580 N  1000 N

4,0	6,0	1,0 - 3,5	10750040060	500	71,95
	8,0	3,0 - 5,5	10750040080	500	79,21
	10,0	5,0 - 7,0	10750040100	500	87,18
	12,0	6,5 - 9,0	10750040120	500	93,39
	16,0	8,5 - 12,5	10750040160	500	110,26
	18,0	12,0 - 14,5	10750040180	500	123,74
	20,0	14,0 - 16,0	10750040200	500	131,58

d_k 12,0 ^{-0,3} **d_m 2,2** **k 1,5** ^{+0,5}  4,1 mm  1250 N  2000 N

4,8	8,0	2,0 - 5,0	10770048080	500	105,23
	10,0	4,0 - 6,5	10770048100	500	113,20
	12,0	6,0 - 8,0	10770048120	500	123,98
	16,0	7,5 - 12,0	10770048160	500	139,91
	18,0	11,5 - 13,5	10770048180	500	152,45
	20,0	12,0 - 15,5	10770048200	250	160,64
	25,0	15,0 - 20,5	10770048250	250	175,29
	30,0	20,0 - 25,0	10770048300	250	191,00

d_k 16,0 ^{-0,3} **d_m 2,7** **k 1,8** ^{+0,5}  4,9 mm  1640 N  2600 N

d	l ⁺¹		Nr.		€/ 1.000
5,0	8,0	2,0 - 5,0	10740050080	500	80,27
	10,0	4,0 - 6,5	10740050100	500	83,31
	12,0	6,0 - 8,0	10740050120	500	89,29
	14,0	7,5 - 10,0	10740050140	500	100,18
	16,0	8,0 - 12,0	10740050160	500	112,14
	20,0	12,0 - 15,5	10740050200	500	147,41
	25,0	15,0 - 20,5	10740050250	500	168,61
	30,0	20,0 - 25,0	10740050300	500	189,35

d_k 11,0 ^{-0,3} **d_m 2,7** **k 1,5** ^{±0,5}  5,1 mm  1820 N  2800 N

5,0	8,0	2,5 - 5,0	10760050080	500	94,21
	10,0	4,0 - 6,5	10760050100	500	102,99
	12,0	6,0 - 8,0	10760050120	500	113,43
	14,0	7,5 - 10,0	10760050140	500	119,05
	16,0	8,0 - 12,0	10760050160	500	124,55
	18,0	11,5 - 13,5	10760050180	500	137,33
	20,0	12,0 - 15,5	10760050200	500	147,05
	25,0	15,0 - 20,5	10760050250	250	175,17
	30,0	20,0 - 25,0	10760050300	250	204,23

d_k 14,0 ^{-0,3} **d_m 2,7** **k 1,5** ^{±0,5}  5,1 mm  1820 N  2800 N

5,0	10,0	4,0 - 6,5	10770050100	500	114,36
	16,0	8,0 - 12,0	10770050160	500	141,32
	20,0	12,0 - 15,5	10770050200	250	170,49
	25,0	15,0 - 20,5	10770050250	250	194,86
	33,0	20,0 - 28,0	10770050330	250	234,94

d_k 16,0 ^{-0,3} **d_m 2,7** **k 1,8** ^{+0,5}  5,1 mm  1820 N  2800 N

6,0	10,0	3,0 - 5,5	10770060100	250	216,19
	16,0	7,0 - 11,0	10770060160	250	219,94
	20,0	11,0 - 15,0	10770060200	250	233,76

d_k 16,0 ^{-0,3} **d_m 3,2** **k 1,8** ^{+0,5}  6,1 mm  2660 N  3500 N